

Uni-Bell Designation	
UNI-B-2	<p>The Uni-Bell Standard, UNI-B-2 is now out of print.</p> <p>The Standard has been replaced by AWWA Standard C900, "Polyvinyl Chloride (PVC) Pressure Pipe and Fabricated Fittings, 4 In. Through 12 In. (100 mm Through 300 mm), for Water Distribution."</p> <p>If you would like to order a copy of AWWA C900, please contact the AWWA bookstore. (www.awwa.org/bookstore)</p>
UNI-B-3	<p>The Uni-Bell Standard, UNI-B-3, "Recommended Practice for the Installation of Polyvinyl Chloride (PVC) Pressure Pipe (Nominal Diameters 4 - 36 Inch)," is now out of print.</p> <p>The Standard has been replaced by AWWA Standard C605, "Underground Installation of Polyvinyl Chloride (PVC) Pressure Pipe and Fittings for Water."</p> <p>If you would like to order a copy of AWWA C605, please contact the AWWA bookstore. (www.awwa.org/bookstore)</p>
UNI-B-4	<p>The Uni-Bell Standard, UNI-B-4, "Recommended Standard Specification for Polyvinyl Chloride (PVC) Plastic Sewer Pipe and Fittings (Nominal Diameters 4 - 15 Inches)," is now out of print.</p> <p>The Standard has been replaced by ASTM Standard D3034, "Standard Specification for Type PSM Poly(Vinyl Chloride) (PVC) Plastic Sewer Pipe and Fittings."</p> <p>If you would like to order a copy of ASTM D3034, please contact the ASTM publications office. (www.astm.org then click the "Standards" button.)</p>
UNI-B-5	<p>The Uni-Bell Standard, UNI-B-5, "Recommended Practice for the Installation of Polyvinyl Chloride (PVC) Plastic Sewer Pipe," is now out of print.</p> <p>The Standard has been replaced by ASTM Standard D2321, "Standard Practice for Underground Installation of Thermoplastic Pipe for Sewers and other Gravity-Flow Applications."</p> <p>If you would like to order a copy of ASTM D2321, please contact the ASTM publications office. (www.astm.org then click the "Standards" button.)</p>

UNI-B-7	<p>The Uni-Bell Standard, UNI-B-7, "Recommended Standard Specification for Polyvinyl Chloride (PVC) Plastic Gravity Sewer Pipe and Fittings (Nominal Diameters 8 - 36 Inches)," is now out of print.</p> <p>The Standard has been replaced by ASTM Standard F679, "Standard Specification for Poly(Vinyl Chloride) (PVC) Large-Diameter Plastic Sewer Pipe and Fittings."</p> <p>If you would like to order a copy of ASTM F679, please contact the ASTM publications office. (www.astm.org then click the "Standards" button.)</p>
UNI-B-10	<p>The Uni-Bell Standard, UNI-B-10, "Recommended Specification for Type PS46 Polyvinyl Chloride (PVC) Plastic Gravity Sewer Pipe and Fittings (Based on Performance Requirements) (Nominal Diameters 4 - 18 Inches)," is now out of print.</p> <p>The Standard has been replaced by ASTM Standard F789, "Standard Specification for Type PS-46 and Type PS-115 Poly(Vinyl Chloride) (PVC) Plastic Gravity Flow Sewer Pipe and Fittings."</p> <p>If you would like to order a copy of ASTM F789, please contact the ASTM publications office. (www.astm.org then click the "Standards" button.)</p>
UNI-B-11	<p>The Uni-Bell Standard, UNI-B-11, "Recommended Specification for Polyvinyl Chloride (PVC) Water Transmission Pipe (Nominal Diameters 14 - 36 Inch)," is now out of print.</p> <p>The Standard has been replaced by AWWA Standard C905, "Polyvinyl Chloride (PVC) Pressure Pipe and Fabricated Fittings, 14 In. Through 48 In. (350 mm Through 1,200 mm) for Water Transmission and Distribution."</p> <p>If you would like to order a copy of AWWA C905, please contact the AWWA bookstore. (www.awwa.org/bookstore)</p>

UNI-B-12	<p>The Uni-Bell Standard, UNI-B-12, "Recommended Standard Specification for Polyvinyl Chloride (PVC) Pressure Fittings," is now out of print.</p> <p>The Standard has been replaced by AWWA Standard C907, "Polyvinyl Chloride (PVC) Pressure Pipe and Fabricated Fittings, 14 In. Through 48 In. (350 mm Through 1,200 mm) for Water Transmission and Distribution."</p> <p>If you would like to order a copy of AWWA C905, please contact the AWWA bookstore. (www.awwa.org/bookstore)</p>
UNI-B-13	<p>The Uni-Bell Standard, UNI-B-13, "Recommended Standard Performance Specification for Joint Restraint Devices for Use With Polyvinyl Chloride (PVC) Pipes is now out of print.</p> <p>The Standard has been replaced by ASTM Standard F1674, "Standard Test Method for Joint Restraint Products for Use With PVC Pipe."</p> <p>If you would like to order a copy of ASTM F1674, please contact the ASTM publications office. (www.astm.org then click the "Standards" button.)</p>
UNI-B-14	<p>The Uni-Bell Standard, UNI-B-14, "Recommended Standard Specification for Fiberglass Overwrapped Polyvinyl Chloride (PVC) Pressure Fittings," is now out of print.</p> <p>This Recommended Standard has been replaced by AWWA C900 and C905.</p> <p>If you would like to order a copy of AWWA C900 and C905, please contact the AWWA bookstore. (www.awwa.org/bookstore)</p>